

Name: _____

Discrete Structures Test #2 S 2009

1) Draw a line to connect each equivalent statement:

- | | |
|--------------------------------|--------------|
| a) $(A \cap B) \cup \emptyset$ | $A \cup A^c$ |
| b) $A \cap A^c$ | $A - B^c$ |
| c) $A - B$ | \emptyset |
| d) U | $A \cap B^c$ |


2) Reduce $A \cup (B \cap C^c)^c \cup C$:

3) Markov chains are employed in algorithmic music composition. In a first-order chain, the states of the system become note or pitch values, completing a transition probability matrix (see below). An algorithm is constructed to produce and output note values based on the transition matrix weightings. Determine the probability if the present note is A, followed by another note, then the next note is Eb. (Hint: a cell in Note^2 .)

Note	A	C#	Eb
A	.1	.6	.3
C#	.25	.05	.7
Eb	.7	.3	0

4) Determine $\sum_{i=-3}^4 a_i 2^i$, $a_3 = 1, a_2 = 0, a_1 = 0, a_0 = 0, a_1 = 0, a_2 = 1, a_3 = 1, a_4 = 1$.

5) Are these two graphs isomorphic? If so label their vertices so that the isomorphism is apparent. If not, list an isomorphic invariant that is violated.



Name: _____

6) The relation $R = \{(a, a), (b, b), (b, c), (b, d), (c, b), (c, c), (c, d), (d, b), (d, c), (d, d)\}$ is an equivalence relation on the set $L = \{a, b, c, d\}$.

a) Draw directed graph for the relation R .

b) If R is reflexive, symmetric and transitive, find the distinct equivalence classes of R .

c) Create an adjacency matrix for R on $L \times L$.

d) Find R^2

7) List the first three terms of the sequence $c_i = (-1)^{i+1} / 2^{i+1}$, for all integers $i \geq 0$:

```
public static void main(String[] args) {
    int[] f = {1,6,2,-9,6};
    int[] g = new int[f.length];
    int a = -2, i;
    g[0] = f[0];
    for(i = 0; i < f.length; i++) {
        System.out.print(" f["+ i + "] = " + f[i]+ (i==f.length-1?
            ".\n":"", "));
    }
    for(i = 1; i < f.length; i++) {
        g[i] = a*g[i-1] + f[i];
    }
    System.out.println((g[i-1]==0 ? " Found root: x = " + a :
        " remainder: " + g[i-1] + "/"(x - " + a + ")"));
}
//output:
f[0] = 1, f[1] = 6, f[2] = 2, f[3] = -9, f[4] = 6.
Found root: x = -2
```

8) What are the final values of g ?

Name: _____

9) Consider the Java bytes $A = 1010\ 1010$, $B = 0101\ 0101$. Convert their sum, $A + B$, to decimal:

10) Complete this Proof by mathematical induction 1) basis step 2) inductive step.

$P(n)$: $1 + 4 + 7 + 10 + \dots + (3n - 2) = (n/2)(3n - 1)$, for all n greater than or equal to 1.

Proof (MI) Basis Step:

$$P(n) : \sum_{i=1}^n (3i - 2) = \frac{n}{2} (3n - 1), \quad \forall n \in \mathbb{Z}, n \geq 1$$

$$P(1) :$$

Inductive Step:

$$\text{Let } P(k) : \sum_{i=1}^k (3i - 2) = \frac{k}{2} (3k - 1), \quad \text{for some integer } k \geq 1.$$

We must show $P(k + 1)$ is true.

$$P(k + 1) : \sum_{i=1}^k (3i - 2) + (3(k + 1) - 2) = \frac{k + 1}{2} (3(k + 1) - 1).$$

$$\text{But } \sum_{i=1}^k (3i - 2) = \frac{k}{2} (3k - 1) \text{ by inductive hypothesis.}$$

So $P(k + 1)$ is then

and we have

$$\frac{3k^2 + 5k + 2}{2} = \frac{3k^2 + 5k + 2}{2}.$$

Name: _____

11) Given the set $H = \{1, 2, 3\}$

- a) Which are equivalence relations?
- b) Which are partial order relations?
- c) Which relations have sources?
List the sources:
- d) Which relations have sinks?
List the sinks:

R	1	2	3
1	0	1	1
2	1	1	0
3	0	0	0

S	1	2	3
1	1	1	1
2	0	1	0
3	1	1	1

T	1	2	3
1	1	0	1
2	0	1	0
3	1	0	1

V	1	2	3
1	0	0	1
2	0	1	0
3	1	0	0

W	1	2	3
1	0	1	0
2	1	0	1
3	0	1	0